

## Ventamatic® Soffit & Gable Vents

- Provide excellent intake ventilation to provide “balance” to attic exhaust ventilation
- Enable constant airflow through the attic when combined with attic exhaust vents
- Function as an essential component of well-balanced attic ventilation systems

### SOFFIT & UNDEREAVE VENTS

- All aluminum construction provides durability and prevents rust
- Fully screened for protection against insects
- Under eave vents have pre-drilled holes for easy installation
- Available in mill, brown, white



Models	Size	Flange	NFA
CX 64	4" x 16"	2.24" x 14.25"	22 sq in
CX 66	6" x 16"	5" x 14.5"	40 sq in
CX 68	8" x 16"	6.5" x 14.5"	58 sq in
CX 8	8 ft lengths	8' x 2.25"	61 sq in per 8'

### MINI VENTS

- Ideal for intake ventilation in smaller structures where soffit area is less than 5" wide
- All aluminum construction for durability
- 1/8" louvered openings meet National Code Standards
- Available in mill finish



Models	Size	Flange	NFA
MV 1	1" diameter	Flange: 1.4"	.235 sq in NFA
MV 2	2" diameter	Flange: 2.5"	.47 sq in NFA
MV 3	3" diameter	Flange: 3.5"	1.34 sq in NFA
MV 4	4" diameter	Flange: 4.5"	2.88 sq in NFA

### WHAT IS "NFA"?

NFA stands for "net free area," a measurement of the unobstructed area through which air can pass freely. The NFA formula takes into account not only the opening of the vent itself, but also considers any screening the vent has to protect the attic from the invasion of birds and rodents. NFA measurements are usually given in square inches. All Ventamatic, Ltd. "static" (i.e., non-powered) attic vents carry NFA measurements.

### WALL & GABLE LOUVERS

- Ideal for intake ventilation in side walls and gable ends
- All aluminum construction provides durability and prevents rust
- Fully screened to protect against insects and rodents
- Available in mill or white finish



Models	Size	Flange	NFA
SGV 88	8" x 8"	10.5" x 10.5"	22 sq in
SGV 1212	12" x 12"	11.25" x 8.75"	53 sq in
SGV 1218	12" x 18"	11.25" x 15"	79 sq in
SGV 1418	14" x 18"	13.25" x 15"	89 sq in
SGV 1424	14" x 24"	13.5" x 21"	119 sq in
SWL 1824	18" x 24"	17.25" x 20.75"	153 sq in
SWL 2430	24" x 30"	23.5" x 27.25"	255 sq in

### RIDGE VENT: Model: SOR4 (18.3" NFA per linear ft)

- Constructed of ultra-violet inhibited injection-molded polypropylene for ultimate in protection against sun and low temperatures
  - Airfoil technology maximizes airflow
  - Unique baffle design provides superior water resistance
  - Molded nail supports
  - Suitable for 3/12 to 14/12 roof pitch installations
  - Available in weathered grey
  - 15.75" wide x 4 ft sections
- Dade County approved*
- Not for use with metric shingles**

